

APPROVED CONTROLS MODEL NUMBER SCHEME	PANEL PLATFORM	NUMBER OF PUMPS	Input Voltage And Phase	FLA	ENCLOSURE	TD/IS	3 Sequential Numbers with Leading Zeroes	FM3297 1124 Supersedes 1223
v13	X	X	X	X	X	— X	X X X	
Pump Controls	1 Pivot Pro	1 Simplex	1 115v 1 Ph	1 0-7	Breakers	1 NEMA1 Painted Steel	8 Time Dose	
	2 Plivot Pro +	2 Duplex	2 230v 1 Ph	2 7-15		2 NEMA1 Plastic	9 Intrinsically Safe	
	3 Pivot	3 Simplex Reversing	3 115/200/230 1 Ph	3 15-20		3 NEMA3R Plastic		
	4 Custom Panel	4 Duplex Reversing	4 200/230/460 3 Ph	4 20-30		4 NEMA4X Plastic		
	5 Pivot RL	5 Triplex or more	5 380 3 Ph	5 0-20		5 NEMA4X Stainless Steel		
	6 LPS		6 575 3 Ph	A 1.0-1.6	Overloads	6 NEMA7 Xproof		
	7 Open		7 200/230v 1 Ph Cap Kit	B 1.6-2.5		7 NEMA4X Painted Steel		
	8 Open	0 No pumps,other, or n/a		C 2.5-4.0		8 NEMA4 Painted Steel		
Accessories	9 Accessories	1 Alarm		D 4.0-6.3		9 NEMA9 Painted Steel		
		2 Jbox		E 6.0-10.0				
		3 Qwik Box		F 9.0-14.0				
		4 Plugger Box		G 13.0-18.0				
		5 Pump Switch		H 17.0-23.0				
		6 Control Switch		Q 20.0-25.0				
		7 Starter Box		R 24.0-32.0				
				S 30.0-40.0				
				T 37.0-50.0				
				U 48.0-63.0				
				V 60.0-70.0				
		0 Other or n/a	0 Other or n/a	0 Other or n/a	0 Other or n/a		0 Other or n/a	

Instructions and Conventions

- Format: 5 digits, dash, 4 digits
30 alpha-numeric digits are available in Syteline 9
- Use numbers only, except for overloads. If letters required, use "left hand" letters, and avoid using small and capital o, capital i, and small L
- Digits before the dash are the Model Number

7/1/2019 v8 Added 0 for Number of Pumps
5/11/2020v9 Changed names of Pivot products
8/16/2021v10 Added "Painted" and "Steel" to enclosure descriptions, and other minor changes
5/25/2022v11 Changed "R" Overload range from 23-32 to 24-32, added ranges S,T, and U and TD/IS column
12/12/2023 v12 Add "Pivot RL"
11/25/2024 v13 Add "V" overload, adjust "U" overload

Examples

31124-0001, Pivot simplex 115v 1Ph 7-15a 4X enclosure.
24224-0001, Pivot Pro + duplex reversing 230v 1Ph 7-15a 4X enclosure
91104-0001, APak Outdoor 115v 4X enclosure
124S4-9001, Pivot Pro duplex 200/230/460 3Ph 30-40a 4X enclosure intrinsically safe